

5-140 Window Seals EPDM / NBR



Advantages

- Window seals are used to mount panes, windows, etc. in doors, casings and machine enclosures.
- They are made of EPDM / NBR. The pane is mounted by simply pressing it into the window seal.
- Additional tools are not required. The pane is inside or outside the enclosure and hence is well-suited for use under high pressure or vacuum conditions.
- **EPDM seals are tested according to UL 157 and UL 50E.**

Materials

- **Rubber quality:** EPDM or Perbunan (NBR), NBR is oil-resistant

Remarks

Please dimension window with 1,5 mm gap circumferentially.
All standard window seals are available from stock.
Note Tolerances!



Window Seals

	Part Number	Material	Colour	Bending radius	Glass thickness	Sheet thickness	Height H	Packaging unit
a)	209-0401.00-00000	rubber/EPDM	black	min 80	4,5 mm	2,4 mm	16,0 mm	100,0 m
b)	209-0402.00-00000	rubber/EPDM	black	min 80	6,5 mm	2,4 mm	16,0 mm	100,0 m
a)	209-0406.00-00000	NBR	black	min 80	4,5 mm	2,4 mm	16,0 mm	100,0 m
b)	209-0407.00-00000	NBR	black	min 80	6,5 mm	2,4 mm	16,0 mm	100,0 m

